

# AVIVO ATF DEXRON III / H

## DESCRIPTION

A premium semi-synthetic transmission fluids formulated with high quality group III base stock with advanced additive system that provides consumers an excellent driving experience.

## PERFORMANCE STANDARDS

DEXRON III / H /M

ALLISON C4

ALLISON TES-389 SCHEDULE ONE

## BENEFITS

1. Excellent oxidation and thermal stability that reduces engine deposits and sludge formation
2. Improves and extends transmission efficiency, smooth

shifting performance and potential fuel savings

3. Keep transmission clean to extend life and performance even under severe operating condition
4. Assist in improved start-up and clean fast lubrication at low ambient temperature

## APPLICATIONS

Recommended for service refill and top-up for passenger cars and light truck automotive transmission requiring Dexron III fluids. Other application includes off high-way transmissions, power steering and other hydraulic systems requiring Allison C-4 or Allison TES-389 fluids

## TYPICAL SPECIFICATIONS

	Test Method	DEXRON III / H
Kinematic Viscosity, cSt	ASTM D445	
@ 40°C		33.0
@ 100°C		7.0
VI	ASTM D2270	170
Flash Point,COC, Deg C	ASTM D92	180
Pour Point, Deg C, max	ASTM D97	-39
Color	visual	red