

AVIVO CI4/SL 15W40

DESCRIPTION

CI4/SL 15W40 is formulated for all heavy-duty diesel engines, using specifically formulated additive package plus premium hydro-finished base oil to address the severe demands of a diesel engine's internal environment. It exceeds the requirements of the following performance levels:

PERFORMANCE LEVELS

API CI4/CH4/CG4/CF4/CF/SL
MACK EO-M PLUS
ACEA E3-96#4/E5-02/E7-04
ACEA A3/B3/B4-02
MB p228.3
MTU TYPE II QUALITY
VW 501/505 QUALITY
VOLVO VDS-3
DETROIT DIESEL 93K215
CUMMINS 20072/77

BENEFITS

1. Reduces ash deposits in hot sections of the engine to prevent ring sticking and loss of power.
2. High oxidation stability protects against sludge and varnish deposits.
3. Complete engine protection against wears, corrosion and rusting, reduces maintenance cost.
4. Cleans engine by strong detergent-dispersant additives.
5. Extended oil drain intervals.

APPLICATIONS

Recommended for moderate and severe service gasoline and diesel mixed fleets, thus reducing the inventory cost.

Diesel and gasoline engines with turbo-charged and heavy-duty applications.

TYPICAL SPECIFICATIONS

SAE	Test Method	15W40
Kinematic Viscosity, cSt @ 40°C @ 100°C	ASTM D445	111 14.9
VI	ASTM D2270	139
Flash Point, COC, min	ASTM D92	218
Pour Point, Deg C, max	ASTM D97	-30
TBN, mgKOH/g	ASTM D2896	9.5